

# DHV-460/860/1660

## Standalone DVR

4ch/8ch/16ch DVR  
Wavelet Compression Format  
UBS 2.0 Backup Storage  
Networking Capability



## SPECIFICATIONS

TV System	DHV-460		DHV-860		DHV-1660	
	PAL	NTSC	PAL	NTSC	PAL	NTSC
Video Input / Loop Through	BNC x 4		BNC x 8		BNC x 16	
Monitor Output			BNC x 1			
Audio Input / Output			RCA x 2			
Compression Format			Wavelet			
Alarm Input	Dry contact x 4		Dry contact x 8		Dry contact x 16	
Control Output			x 1 (max. 1A, AC/DC)			
Comunication Port			1 RS232			
Network Interface			1 RJ45(10/100 Base-T)			
Display Rate	100 pps	120 pps	200pps	240 pps	400 pps	480 pps
Recording Resolution	CIF, 1/2 D1		CIF, 1/2 D1		CIF, 1/2 D1	
Recording Rate (max)	100 pps	120 pps	100 pps	120 pps	100 pps	120 pps
Recording Quality			Low, Fair, Good, Better, Best			
Recording Mode			24hrs, Schedule, Alarm/Motion Trigger			
Display Resolution			PAL:720x576 ; NTSC:720x480 ; 520TVL			
Camera Title			Up to 8 characters			
Video Adjustment			Color, Contrast, Brightness on each camera			
Hard Disk			IDE type x1 (support 80, 120, 160, 200, 250, 400GB)			
Operation Interface			Keypad			
Playback Control			FF, Play, Rewind, Speed Up & Down			
Search Playback Index			Date/time, Alarm, Motion			
System Setup / OSD			Multi-language			
System Alarm			Video loss, Motion, Alarm, HardDrive full			
Backup / Copy			USB 2.0			
Power Supply			90~260 Vac Switching Power(50/60Hz)			
Power Consumption	< 30 W		< 40 W		< 40 W	
Operation Temperature			- 10° C~+45° C			
Dimension			425 W x 300D x 44H mm (16.74W x 11.82D x 1.74H inches)			
Net Weight(Without HDD)	< 4 kg (8.9 lbs)		< 4.5 kg (10 lbs)		< 4.6 kg (10.2 lbs)	

## DIMENSIONS

### ◆ Front View



### ◆ Rear View

